


▲ TOP 7000 Pro | ▲ TOP 700 | ▲ TOP 5100 | ▲ TOP 3100

DOSING SYSTEMS


THE PERFECT DOSAGE FOR
EVERY LSR APPLICATION.



PRODUCT OVERVIEW DOSING SYSTEMS




TOP CONVEYED
TOP MIXED
TOP IN USE



	TOP 7000 Pro		TOP 700	TOP 5100	TOP 3100
Pump unit	M	S	S	M	M
Dimensions L/W/H (mm)	1150 x 790 x 1965 (2445)	1150 x 790 x 1965 (2445)	799 x 600 x 1775	1150 x 790 x 1965 (2445)	1260 x 1213 x 1900 (2672)
Drum sizes (liter gallons)	200/20 55/5	200/20 55/5	20 5	200/20 55/5	200/20 55/5
Useable materials [Pas]	0,001 to 3000	0,001 to 2000	0,001 to 2000	0,001 to 3000	0,001 to 3000
Delivery rate per component @ 2,7 Pas	> 2350 cm³ /min	> 2500 cm³ /min	> 2500 cm³ /min	> 2350 cm³ /min	> 2350 cm³ /min
Max. delivery pressure	230 bar / 3336 psi	210 bar / 3046 psi	210 bar / 3046 psi	230 bar / 3336 psi	200 bar / 2900 psi
Power supply	100 - 264 VAC, 4 A	100 - 264 VAC, 4 A	100 - 264 VAC, 4 A	100 - 264 VAC, 4 A	100 - 264 VAC, 4 A
Air supply	6 bar – 1000 NL / min (1/2“)	6 bar – 1000 NL / min (1/2“)	6 bar – 1000 NL / min (1/2“)	6 bar – 1000 NL / min (1/2“)	6 bar – 1000 NL / min (1/2“)
Interfaces for additive lines	2 standard to 6 optional	2 standard to 6 optional	2 standard to 6 optional	2 standard to 6 optional	1 standard
Static mixer	1 standard (Expandable)	1 standard (Expandable)	1 standard (Expandable)	1 standard (Expandable)	1standard (Expandable)
Purging volume up to	20 g	20 g	20 g	20 g	20 g
Material utilization per container up to	99.6 %	99.8 %	99 %	99.6 %	99.6 %
Volume counter per component A/B	512.000 Imp/L	512.000 Imp/L	512.000 Imp/L	256.000 Imp/L	64.000 Imp/L
Volume counter additive (10.240.000 Imp/l)	▲	▲	▲	▲	▲
Certifications / Declaration of Conformity	CE / UL / RoHS	CE / UL / RoHS	CE / UL / RoHS	CE / UL / RoHS	CE / UL / RoHS
Drum change 3 sides (180°) in 2 minutes	■	■	■	■	✗
Guided drum change	■	■	■	■	■
Fully automatic drum change from the edge of the drum	■	■	■	✗	✗
Automatic material detection when changing drums	■	■	■	▲	✗
Automatic drum ventilation	■	■	■	■	✗
Closed loop drum ventilation	■	■	■	▲	✗
Automatic purging	■	■	■	▲	✗
Air detection	■	■	■	■	■
Automatic de-airing	▲	▲	▲	▲	✗
Eco-Mix (Simultaneous drum emptying)	■	■	■	■	■
Fix-Mix (Freely selectable mixing ratio)	■	■	■	▲	▲
Shore-Mix (Adjustable shore hardness)	▲	▲	▲	▲	✗
LSR Select (adjustable cross-linking speed)	▲	▲	▲	▲	✗
Simplex (1 dosing system to 2 injection molding machines)	▲	▲	▲	▲	▲
Tandem (2 dosing systems in alternating operation = no production downtime)	▲	▲	▲	▲	▲
Process documentation USB	■	■	■	■	■
Process documentation OPC UA	■	■	■	▲	▲
Euromap 82.3	■	■	■	▲	✗
Remote maintenance via VNC	■	■	■	▲	▲
Premium Connectivity	▲	▲	▲	▲	▲
Barcode drum detection	▲	▲	▲	▲	▲
Wheels	■	■	■	▲	▲
Customized paint work	▲	▲	▲	▲	✗
Warranty	24 month	24 month	24 month	24 month	12 month

■ STANDARD | ▲ OPTIONAL | ✗ NOT POSSIBLE

DOSING TECHNOLOGY.
MOLDING TECHNOLOGY.
TURNKEY SOLUTIONS.
PRODUCTION SOLUTIONS.



www.elmet.com

ELMET 09/2026 | EN

FOR MORE THAN 30 YEARS

we have been developing customized, innovative solutions for our customers. As a global high-end full system and service provider for the processing and dosing of liquid silicone (LSR), we at ELMET are among the leading specialists in this field.



SMART SILICONE SOLUTIONS

ELMET Elastomere Produktions- und Dienstleistungs GmbH

Tulpenstraße 21 | 4064 Oftering | Austria | T: +43 7221 74577-0 | E: office@elmet.com

ELMET NORTH AMERICA INC.

712 Terminal Road, Lansing, MI 48906 USA
Local: 517-664-9011
Toll Free: 866-628-6499
E: office@elmet.com

ELMET GREATER CHINA

No. 20, Renxiang St., Dali Dist.,
Taichung City
T: +866-979-885-628
E: office@elmet.com

ELMET JAPAN

3-902-4, Yashirogaoka, Meito-ku,
Nagoya-shi, Aichi-ken 4650051
T: +81-70-7793-1895
E: office@elmet.com